

# Polarization Maintaining Fiber Patchcord

## Product Overview

PM fiber patchcords with good polarization maintenance and low loss for different wavelength ranges

## SPECIFICATIONS

Wavelength range	1310, 1550	980, 1060	850	780
Extinction ratio	>23dB	>23dB	>22dB	>22dB
Insertion loss	<0.3dB	<0.5dB	<0.8dB	<0.8dB
Key orientation	Slow axis			
Return loss	>50dB			
Fiber type	PM1310, PM1550	PM980	PM850	PM780
Operating temperature range	-20°C to 70°C			
Transportation/storage	-40°C to 80°C			

## Ordering Information

<b>P</b>	<b>M</b>	<b>P</b>	<b>C</b>	-	<input type="text"/>	-	<input type="text"/>	-	<input type="text"/>	-	<input type="text"/>	-	<input type="text"/>	-	<input type="text"/>
					Wavelength:		Input connector:	Output connector:	Fiber type:	Cable type:	Length:				
					15 – 1530nm		1 – FC/UPC	1 – FC/UPC	1 – PM780	0 – none	1 – 1m				
					13 – 1310 nm		2 – FC/APC	2 – FC/APC	2 – PM850	1 – 900um loose tube	2 – 2m				
					10 – 1060 nm		3 – SC/UPC	3 – SC/UPC	3 – PM980		C – customer defined				
					09 – 980nm		4 – SC/APC	4 – SC/APC	4 – PM1310						
					08 – 850nm		5 – LC/UPC	5 – LC/UPC	5 – PM1550						
					07 – 780nm		6 – LC/APC								

For more information please contact Phoenix sales:  
[sales@phoenixphotonics.com](mailto:sales@phoenixphotonics.com) or visit us at  
[www.phoenixphotonics.com](http://www.phoenixphotonics.com)